SAFETY DATA SHEET

IDENTITY (As Used On Label) Clarus	s PRO Screar	nin' 8 (8-	-14-1)		Date Prepared 6/15/2015	
SECTION 1. Product and Company Identification	ı	1				
Distributor's Name Nutrients PLUS, LLC		Emerge	ency Tel. N	0	800-424-9300 Chemtrec	
Address (Number, Street, City, State and Zip) 2133 Upton Drive Ste 126-509, Virginia Beach, VA 23454		Tel. No. For Information			888-675-7515 (x4)	
SECTION 2. Composition and Information on Ing	redients					
dentity: Common Name (CAS #)		OSHA PEL	ACGIH TLV	Other Limits Recor	mmended	
BioSolids (308066-19-5)	Total Dust Exposure	15 mg/m ³	10mg/m ³			
	Respirable Fraction	5mg/m ³	3mg/m ³			
Composted Poultry Manure (N/A)		N/A	N/A			
mmonium Sulfate (7783-20-2)		N/A	N/A			
mmonium Phosphate (7783-28-0)		N/A	N/A			
Trace metals can be detected in the finished product in quantities		n most less th	an 0.1%.			
SECTION 3. Health Hazards Identification Primary route(s) of entry	Inhalation (dus	st) Eve and S	Skin Contact Ir	gestion		
Signs and Symptoms of Exposure	Contact with th Ingestion of ex mucus without	Inhalation (dust), Eye and Skin Contact, Ingestion Inhaled dust may cause some respiratory irritation. Contact with the eye and skin may produce irritation and/or redness. Ingestion of extremely small quantities of dust could be possible when mixed with nasal and throat mucus without symptoms. Individuals with respiratory ailments, such as asthma, may be particularly sensitive to dust exposure.				
Carcinogens		This product may contain traces of substances considered to be carcinogens by OSHA, IARC, NTP, however not in quantities greater than 0.1%.				
Warning MAY BE HARMFUL IF SWALLOWED MAY CAUSE MILD SKIN IRRITATION MAY CAUSE EYE IRRITATION MAY CAUSE RESPIRATORY IRRITATION						
SECTION 4. First Aid Measures						
nhalation		-			rmal breathing does not return or	
ngestion	This is not an e	symptoms of illness occur obtain medical attention. This is not an expected route of exposure, however if a significant quantity is ingested, consult with a physician.				
ye Contact					es. Lift eyelids while flushing to allow ed) Obtain medical attention if	
Skin Contact	Wash skin thor	roughly with s	soap and water	until product is remo	oved	

SAFETY DATA SHEET

Boiling Range	
	N/A
Melting Point	N/A
Evaporation Rate	N/A
Vapor Pressure	N/A
Vapor Density	N/A
Bulk Density	35 to 45 lbs/ft3
Percent Moisture	2 to 5%
Odor	Earthy, organic
Solubility	Slight
Reactivity in Water	Non reactive. Small amounts of water may cause this product to heat by encouraging biological activity. Keep dry.
Appearance	Blend of ingredients listed above.
% Volatile	Negligible.
SECTION 6. Fire and Explosion Hazard Da	
Flash Point	N/A
Autoignition Temperature	N/D N/D
Flammable Limits in Air, % by Volume	N/D Combustible solid may generate carbon, sulfur and nitrogen oxides during combustion.
	Dust passing the Tyler Screen 40 mesh possesses the following characteristics:
Explosion	(dust used in this test was generated during handling)
	Explosion Severity- 0.91 Minimum Explosive Concentration - 0.105 oz./ft3
	Minimum Ignition Temperatures - dust cloud - 365 degrees C
Tation de la constante	dust layer - 170 degrees C
	dust layer - 170 degrees C Water, dry chemical, foam
	dust layer - 170 degrees C Water, dry chemical, foam None, normal full protective gear with self-contained breathing apparatus as in any firefighting
Special Fire Fighting Procedures	dust layer - 170 degrees C Water, dry chemical, foam
Special Fire Fighting Procedures	dust layer - 170 degrees C Water, dry chemical, foam None, normal full protective gear with self-contained breathing apparatus as in any firefighting
Special Fire Fighting Procedures SECTION 7. Stability & Reactivity Data	dust layer - 170 degrees C Water, dry chemical, foam None, normal full protective gear with self-contained breathing apparatus as in any firefighting situation.
Special Fire Fighting Procedures SECTION 7. Stability & Reactivity Data Stability	dust layer - 170 degrees C Water, dry chemical, foam None, normal full protective gear with self-contained breathing apparatus as in any firefighting situation. Stable under ordinary conditions and use.
Special Fire Fighting Procedures SECTION 7. Stability & Reactivity Data Stability	dust layer - 170 degrees C Water, dry chemical, foam None, normal full protective gear with self-contained breathing apparatus as in any firefighting situation. Stable under ordinary conditions and use. Do not mix with oxidizers such as nitrate fertilizers, as this may initiate and/or accelerate
Special Fire Fighting Procedures SECTION 7. Stability & Reactivity Data Stability ncompatibilities	dust layer - 170 degrees C Water, dry chemical, foam None, normal full protective gear with self-contained breathing apparatus as in any firefighting situation. Stable under ordinary conditions and use. Do not mix with oxidizers such as nitrate fertilizers, as this may initiate and/or accelerate combustion.
Special Fire Fighting Procedures SECTION 7. Stability & Reactivity Data Stability ncompatibilities Conditions to Avoid	dust layer - 170 degrees C Water, dry chemical, foam None, normal full protective gear with self-contained breathing apparatus as in any firefighting situation. Stable under ordinary conditions and use. Do not mix with oxidizers such as nitrate fertilizers, as this may initiate and/or accelerate combustion. Heat, sparks, open flames, oxidizing agents
Special Fire Fighting Procedures SECTION 7. Stability & Reactivity Data Stability ncompatibilities Conditions to Avoid Hazardous Decomposition Products	dust layer - 170 degrees C Water, dry chemical, foam None, normal full protective gear with self-contained breathing apparatus as in any firefighting situation. Stable under ordinary conditions and use. Do not mix with oxidizers such as nitrate fertilizers, as this may initiate and/or accelerate combustion. Heat, sparks, open flames, oxidizing agents Oxides of carbon, sulfur, and nitrogen may be formed as a result of combustion.
Special Fire Fighting Procedures SECTION 7. Stability & Reactivity Data Stability ncompatibilities Conditions to Avoid Hazardous Decomposition Products Hazardous Polymerzation	dust layer - 170 degrees C Water, dry chemical, foam None, normal full protective gear with self-contained breathing apparatus as in any firefighting situation. Stable under ordinary conditions and use. Do not mix with oxidizers such as nitrate fertilizers, as this may initiate and/or accelerate combustion. Heat, sparks, open flames, oxidizing agents Oxides of carbon, sulfur, and nitrogen may be formed as a result of combustion. Will not occur
Special Fire Fighting Procedures SECTION 7. Stability & Reactivity Data Stability Incompatibilities Conditions to Avoid Hazardous Decomposition Products Hazardous Polymerzation	dust layer - 170 degrees C Water, dry chemical, foam None, normal full protective gear with self-contained breathing apparatus as in any firefighting situation. Stable under ordinary conditions and use. Do not mix with oxidizers such as nitrate fertilizers, as this may initiate and/or accelerate combustion. Heat, sparks, open flames, oxidizing agents Oxides of carbon, sulfur, and nitrogen may be formed as a result of combustion. Will not occur
Special Fire Fighting Procedures SECTION 7. Stability & Reactivity Data Stability Incompatibilities Conditions to Avoid Hazardous Decomposition Products Hazardous Polymerzation SECTION 8. Special Precautions and Spill F	dust layer - 170 degrees C Water, dry chemical, foam None, normal full protective gear with self-contained breathing apparatus as in any firefighting situation. Stable under ordinary conditions and use. Do not mix with oxidizers such as nitrate fertilizers, as this may initiate and/or accelerate combustion. Heat, sparks, open flames, oxidizing agents Oxides of carbon, sulfur, and nitrogen may be formed as a result of combustion. Will not occur
Special Fire Fighting Procedures SECTION 7. Stability & Reactivity Data Stability Incompatibilities Conditions to Avoid Hazardous Decomposition Products Hazardous Polymerzation SECTION 8. Special Precautions and Spill I Release or spill	dust layer - 170 degrees C Water, dry chemical, foam None, normal full protective gear with self-contained breathing apparatus as in any firefighting situation. Stable under ordinary conditions and use. Do not mix with oxidizers such as nitrate fertilizers, as this may initiate and/or accelerate combustion. Heat, sparks, open flames, oxidizing agents Oxides of carbon, sulfur, and nitrogen may be formed as a result of combustion. Will not occur Procedures Clean up and use per instructions or follow local, state and federal regulations for disposal
Special Fire Fighting Procedures SECTION 7. Stability & Reactivity Data Stability Incompatibilities Conditions to Avoid Hazardous Decomposition Products Hazardous Polymerzation SECTION 8. Special Precautions and Spill I Release or spill	dust layer - 170 degrees C Water, dry chemical, foam None, normal full protective gear with self-contained breathing apparatus as in any firefighting situation. Stable under ordinary conditions and use. Do not mix with oxidizers such as nitrate fertilizers, as this may initiate and/or accelerate combustion. Heat, sparks, open flames, oxidizing agents Oxides of carbon, sulfur, and nitrogen may be formed as a result of combustion. Will not occur Procedures Clean up and use per instructions or follow local, state and federal regulations for disposal of non-hazardous heat-dried sewage sludge.
Special Fire Fighting Procedures SECTION 7. Stability & Reactivity Data Stability Incompatibilities Conditions to Avoid Hazardous Decomposition Products Hazardous Polymerzation SECTION 8. Special Precautions and Spill I Release or spill	dust layer - 170 degrees C Water, dry chemical, foam None, normal full protective gear with self-contained breathing apparatus as in any firefighting situation. Stable under ordinary conditions and use. Do not mix with oxidizers such as nitrate fertilizers, as this may initiate and/or accelerate combustion. Heat, sparks, open flames, oxidizing agents Oxides of carbon, sulfur, and nitrogen may be formed as a result of combustion. Will not occur Procedures Clean up and use per instructions or follow local, state and federal regulations for disposal of non-hazardous heat-dried sewage sludge. Keep biosolid pellets dry during storage, as moisture content that exceeds 10% (by weight) will
Special Fire Fighting Procedures SECTION 7. Stability & Reactivity Data Stability Incompatibilities Conditions to Avoid Hazardous Decomposition Products Hazardous Polymerzation SECTION 8. Special Precautions and Spill Release or spill	dust layer - 170 degrees C Water, dry chemical, foam None, normal full protective gear with self-contained breathing apparatus as in any firefighting situation. Stable under ordinary conditions and use. Do not mix with oxidizers such as nitrate fertilizers, as this may initiate and/or accelerate combustion. Heat, sparks, open flames, oxidizing agents Oxides of carbon, sulfur, and nitrogen may be formed as a result of combustion. Will not occur Procedures Clean up and use per instructions or follow local, state and federal regulations for disposal of non-hazardous heat-dried sewage sludge. Keep biosolid pellets dry during storage, as moisture content that exceeds 10% (by weight) will cause spontaneous biological heating potentially leading to combustion. Equipment used to
Special Fire Fighting Procedures SECTION 7. Stability & Reactivity Data Stability ncompatibilities Conditions to Avoid Hazardous Decomposition Products Hazardous Polymerzation SECTION 8. Special Precautions and Spill Release or spill	dust layer - 170 degrees C Water, dry chemical, foam None, normal full protective gear with self-contained breathing apparatus as in any firefighting situation. Stable under ordinary conditions and use. Do not mix with oxidizers such as nitrate fertilizers, as this may initiate and/or accelerate combustion. Heat, sparks, open flames, oxidizing agents Oxides of carbon, sulfur, and nitrogen may be formed as a result of combustion. Will not occur Procedures Clean up and use per instructions or follow local, state and federal regulations for disposal of non-hazardous heat-dried sewage sludge. Keep biosolid pellets dry during storage, as moisture content that exceeds 10% (by weight) will cause spontaneous biological heating potentially leading to combustion. Equipment used to process biosolids pellets should be electrically bonded to ground. Use electrically conductive
Special Fire Fighting Procedures SECTION 7. Stability & Reactivity Data Stability ncompatibilities Conditions to Avoid Hazardous Decomposition Products Hazardous Polymerzation SECTION 8. Special Precautions and Spill Release or spill	dust layer - 170 degrees C Water, dry chemical, foam None, normal full protective gear with self-contained breathing apparatus as in any firefighting situation. Stable under ordinary conditions and use. Do not mix with oxidizers such as nitrate fertilizers, as this may initiate and/or accelerate combustion. Heat, sparks, open flames, oxidizing agents Oxides of carbon, sulfur, and nitrogen may be formed as a result of combustion. Will not occur Procedures Clean up and use per instructions or follow local, state and federal regulations for disposal of non-hazardous heat-dried sewage sludge. Keep biosolid pellets dry during storage, as moisture content that exceeds 10% (by weight) will cause spontaneous biological heating potentially leading to combustion. Equipment used to process biosolids pellets should be electrically bonded to ground. Use electrically conductive pneumatic transport lines to prevent static electricity discharge. Enclosed process equipment should contain relief vents, explosion suppression systems, and or an oxygen deficient atmosphere Prevent an accumulation of dust or dust leaks in process equipment. Keep all ignition sources away
Special Fire Fighting Procedures SECTION 7. Stability & Reactivity Data Stability Incompatibilities Conditions to Avoid Hazardous Decomposition Products Hazardous Polymerzation SECTION 8. Special Precautions and Spill F Release or spill Precautions to be taken in handling and storage	dust layer - 170 degrees C Water, dry chemical, foam None, normal full protective gear with self-contained breathing apparatus as in any firefighting situation. Stable under ordinary conditions and use. Do not mix with oxidizers such as nitrate fertilizers, as this may initiate and/or accelerate combustion. Heat, sparks, open flames, oxidizing agents Oxides of carbon, sulfur, and nitrogen may be formed as a result of combustion. Will not occur Procedures Clean up and use per instructions or follow local, state and federal regulations for disposal of non-hazardous heat-dried sewage sludge. Keep biosolid pellets dry during storage, as moisture content that exceeds 10% (by weight) will cause spontaneous biological heating potentially leading to combustion. Equipment used to process biosolids pellets should be electrically bonded to ground. Use electrically conductive pneumatic transport lines to prevent static electricity discharge. Enclosed process equipment should contain relief vents, explosion suppression systems, and or an oxygen deficient atmosphere
Special Fire Fighting Procedures SECTION 7. Stability & Reactivity Data Stability Incompatibilities Conditions to Avoid Hazardous Decomposition Products Hazardous Polymerzation SECTION 8. Special Precautions and Spill P Release or spill Precautions to be taken in handling and storage SECTION 9. Exposure Controls/ Personal Protection	dust layer - 170 degrees C Water, dry chemical, foam None, normal full protective gear with self-contained breathing apparatus as in any firefighting situation. Stable under ordinary conditions and use. Do not mix with oxidizers such as nitrate fertilizers, as this may initiate and/or accelerate combustion. Heat, sparks, open flames, oxidizing agents Oxides of carbon, sulfur, and nitrogen may be formed as a result of combustion. Will not occur Procedures Clean up and use per instructions or follow local, state and federal regulations for disposal of non-hazardous heat-dried sewage sludge. Keep biosolid pellets dry during storage, as moisture content that exceeds 10% (by weight) will cause spontaneous biological heating potentially leading to combustion. Equipment used to process biosolids pellets should be electrically bonded to ground. Use electrically conductive pneumatic transport lines to prevent static electricity discharge. Enclosed process equipment should contain relief vents, explosion suppression systems, and or an oxygen deficient atmosphere Prevent an accumulation of dust or dust leaks in process equipment. Keep all ignition sources away from this product.
Special Fire Fighting Procedures SECTION 7. Stability & Reactivity Data Stability Incompatibilities Conditions to Avoid Hazardous Decomposition Products Hazardous Polymerzation SECTION 8. Special Precautions and Spill F Release or spill Precautions to be taken in handling and storage SECTION 9. Exposure Controls/ Personal Protection Engineering Controls	dust layer - 170 degrees C Water, dry chemical, foam None, normal full protective gear with self-contained breathing apparatus as in any firefighting situation. Stable under ordinary conditions and use. Do not mix with oxidizers such as nitrate fertilizers, as this may initiate and/or accelerate combustion. Heat, sparks, open flames, oxidizing agents Oxides of carbon, sulfur, and nitrogen may be formed as a result of combustion. Will not occur Procedures Clean up and use per instructions or follow local, state and federal regulations for disposal of non-hazardous heat-dried sewage sludge. Keep biosolid pellets dry during storage, as moisture content that exceeds 10% (by weight) will cause spontaneous biological heating potentially leading to combustion. Equipment used to process biosolids pellets should be electrically bonded to ground. Use electrically conductive pneumatic transport lines to prevent static electricity discharge. Enclosed process equipment should contain relief vents, explosion suppression systems, and or an oxygen deficient atmosphere Prevent an accumulation of dust or dust leaks in process equipment. Keep all ignition sources away from this product. Dust collection equipment must be used in order to maintain dust levels below exposure limits
Special Fire Fighting Procedures SECTION 7. Stability & Reactivity Data Stability Incompatibilities Conditions to Avoid Hazardous Decomposition Products Hazardous Polymerzation SECTION 8. Special Precautions and Spill F Release or spill Precautions to be taken in handling and storage SECTION 9. Exposure Controls/ Personal Protection Engineering Controls /entilation Procedure	dust layer - 170 degrees C Water, dry chemical, foam None, normal full protective gear with self-contained breathing apparatus as in any firefighting situation. Stable under ordinary conditions and use. Do not mix with oxidizers such as nitrate fertilizers, as this may initiate and/or accelerate combustion. Heat, sparks, open flames, oxidizing agents Oxides of carbon, sulfur, and nitrogen may be formed as a result of combustion. Will not occur Procedures Clean up and use per instructions or follow local, state and federal regulations for disposal of non-hazardous heat-dried sewage sludge. Keep biosolid pellets dry during storage, as moisture content that exceeds 10% (by weight) will cause spontaneous biological heating potentially leading to combustion. Equipment used to process biosolids pellets should be electrically bonded to ground. Use electrically conductive pneumatic transport lines to prevent static electricity discharge. Enclosed process equipment should contain relief vents, explosion suppression systems, and or an oxygen deficient atmosphere Prevent an accumulation of dust or dust leaks in process equipment. Keep all ignition sources away from this product. Dust collection equipment must be used in order to maintain dust levels below exposure limits Remove dust with fans or ventilation suction lines
Section 9. Exposure Controls/ Personal Protection Engineering Controls	dust layer - 170 degrees C Water, dry chemical, foam None, normal full protective gear with self-contained breathing apparatus as in any firefighting situation. Stable under ordinary conditions and use. Do not mix with oxidizers such as nitrate fertilizers, as this may initiate and/or accelerate combustion. Heat, sparks, open flames, oxidizing agents Oxides of carbon, sulfur, and nitrogen may be formed as a result of combustion. Will not occur Procedures Clean up and use per instructions or follow local, state and federal regulations for disposal of non-hazardous heat-dried sewage sludge. Keep biosolid pellets dry during storage, as moisture content that exceeds 10% (by weight) will cause spontaneous biological heating potentially leading to combustion. Equipment used to process biosolids pellets should be electrically bonded to ground. Use electrically conductive pneumatic transport lines to prevent static electricity discharge. Enclosed process equipment should contain relief vents, explosion suppression systems, and or an oxygen deficient atmosphere Prevent an accumulation of dust or dust leaks in process equipment. Keep all ignition sources away from this product. Dust collection equipment must be used in order to maintain dust levels below exposure limits Remove dust with fans or ventilation suction lines
Section 9. Exposure Controls/ Personal Protection Engineering Controls	dust layer - 170 degrees C Water, dry chemical, foam None, normal full protective gear with self-contained breathing apparatus as in any firefighting situation. Stable under ordinary conditions and use. Do not mix with oxidizers such as nitrate fertilizers, as this may initiate and/or accelerate combustion. Heat, sparks, open flames, oxidizing agents Oxides of carbon, sulfur, and nitrogen may be formed as a result of combustion. Will not occur Procedures Clean up and use per instructions or follow local, state and federal regulations for disposal of non-hazardous heat-dried sewage sludge. Keep biosolid pellets dry during storage, as moisture content that exceeds 10% (by weight) will cause spontaneous biological heating potentially leading to combustion. Equipment used to process biosolids pellets should be electrically bonded to ground. Use electrical process equipment should contain relief vents, explosion suppression systems, and or an oxygen deficient atmosphere Prevent an accumulation of dust or dust leaks in process equipment. Keep all ignition sources away from this product. Dust collection equipment must be used in order to maintain dust levels below exposure limits Remove dust with fans or ventilation suction lines Housekeeping procedures must be adequate to minimize dust accumulation on equipment and indoor surfaces. Dust collection containers must be emptied carefully to minimize air-borne
Special Fire Fighting Procedures SECTION 7. Stability & Reactivity Data Stability Incompatibilities Conditions to Avoid Hazardous Decomposition Products Hazardous Polymerzation SECTION 8. Special Precautions and Spill F Release or spill Precautions to be taken in handling and storage SECTION 9. Exposure Controls/ Personal Protection Engineering Controls /entilation Procedure	dust layer - 170 degrees C Water, dry chemical, foam None, normal full protective gear with self-contained breathing apparatus as in any firefighting situation. Stable under ordinary conditions and use. Do not mix with oxidizers such as nitrate fertilizers, as this may initiate and/or accelerate combustion. Heat, sparks, open flames, oxidizing agents Oxides of carbon, sulfur, and nitrogen may be formed as a result of combustion. Will not occur Procedures Clean up and use per instructions or follow local, state and federal regulations for disposal of non-hazardous heat-dried sewage sludge. Keep biosolid pellets dry during storage, as moisture content that exceeds 10% (by weight) will cause spontaneous biological heating potentially leading to combustion. Equipment used to process biosolids pellets should be electrically bonded to ground. Use electrically conductive pneumatic transport lines to prevent static electricity discharge. Enclosed process equipment should contain relief vents, explosion suppression systems, and or an oxygen deficient atmosphere Prevent an accumulation of dust or dust leaks in process equipment. Keep all ignition sources away from this product. Dust collection equipment must be used in order to maintain dust levels below exposure limits Remove dust with fans or ventilation suction lines Housekeeping procedures must be adequate to minimize dust accumulation on equipment and indoor surfaces. Dust collection containers must be emptied carefully to minimize air-borne particles and exposure. Good personal hygiene practices must also be followed,
Special Fire Fighting Procedures SECTION 7. Stability & Reactivity Data Stability Incompatibilities Conditions to Avoid Itazardous Decomposition Products Itazardous Polymerzation SECTION 8. Special Precautions and Spill I Release or spill Precautions to be taken in handling and storage SECTION 9. Exposure Controls/ Personal Protection Engineering Controls /entilation Procedure Nork Practice Controls	dust layer - 170 degrees C Water, dry chemical, foam None, normal full protective gear with self-contained breathing apparatus as in any firefighting situation. Stable under ordinary conditions and use. Do not mix with oxidizers such as nitrate fertilizers, as this may initiate and/or accelerate combustion. Heat, sparks, open flames, oxidizing agents Oxides of carbon, sulfur, and nitrogen may be formed as a result of combustion. Will not occur Procedures Clean up and use per instructions or follow local, state and federal regulations for disposal of non-hazardous heat-dried sewage sludge. Keep biosolid pellets dry during storage, as moisture content that exceeds 10% (by weight) will cause spontaneous biological heating potentially leading to combustion. Equipment used to process biosolids pellets should be electrically bonded to ground. Use electrically conductive pneumatic transport lines to prevent static electricity discharge. Enclosed process equipment should contain relief vents, explosion suppression systems, and or an oxygen deficient atmosphere Prevent an accumulation of dust or dust leaks in process equipment. Keep all ignition sources away from this product. Dust collection equipment must be used in order to maintain dust levels below exposure limits Remove dust with fans or ventilation suction lines Housekeeping procedures must be adequate to minimize dust accumulation on equipment and indoor surfaces. Dust collection containers must be emptied carefully to minimize air-borne particles and exposure. Good personal hygiene practices must also be followed,
Special Fire Fighting Procedures SECTION 7. Stability & Reactivity Data Stability Incompatibilities Conditions to Avoid Integration In	dust layer - 170 degrees C Water, dry chemical, foam None, normal full protective gear with self-contained breathing apparatus as in any firefighting situation. Stable under ordinary conditions and use. Do not mix with oxidizers such as nitrate fertilizers, as this may initiate and/or accelerate combustion. Heat, sparks, open flames, oxidizing agents Oxides of carbon, sulfur, and nitrogen may be formed as a result of combustion. Will not occur Procedures Clean up and use per instructions or follow local, state and federal regulations for disposal of non-hazardous heat-dried sewage sludge. Keep biosolid pellets dry during storage, as moisture content that exceeds 10% (by weight) will cause spontaneous biological heating potentially leading to combustion. Equipment used to process biosolids pellets should be electrically bonded to ground. Use electrically conductive pneumatic transport lines to prevent static electricity discharge. Enclosed process equipment should contain relief vents, explosion suppression systems, and or an oxygen deficient atmosphere Prevent an accumulation of dust or dust leaks in process equipment. Keep all ignition sources away from this product. Dust collection equipment must be used in order to maintain dust levels below exposure limits Remove dust with fans or ventilation suction lines Housekeeping procedures must be adequate to minimize dust accumulation on equipment and indoor surfaces. Dust collection containers must be emptied carefully to minimize air-borne particles and exposure. Good personal hygiene practices must also be followed,
Special Fire Fighting Procedures SECTION 7. Stability & Reactivity Data Stability Incompatibilities Conditions to Avoid Hazardous Decomposition Products Hazardous Polymerzation SECTION 8. Special Precautions and Spill I Release or spill Precautions to be taken in handling and storage SECTION 9. Exposure Controls/ Personal Protection Engineering Controls Ventilation Procedure Work Practice Controls	dust layer - 170 degrees C Water, dry chemical, foam None, normal full protective gear with self-contained breathing apparatus as in any firefighting situation. Stable under ordinary conditions and use. Do not mix with oxidizers such as nitrate fertilizers, as this may initiate and/or accelerate combustion. Heat, sparks, open flames, oxidizing agents Oxides of carbon, sulfur, and nitrogen may be formed as a result of combustion. Will not occur Procedures Clean up and use per instructions or follow local, state and federal regulations for disposal of non-hazardous heat-dried sewage sludge. Keep biosolid pellets dry during storage, as moisture content that exceeds 10% (by weight) will cause spontaneous biological heating potentially leading to combustion. Equipment used to process biosolids pellets should be electrically bonded to ground. Use electrically conductive pneumatic transport lines to prevent static electricity discharge. Enclosed process equipment should contain relief vents, explosion suppression systems, and or an oxygen deficient atmosphere Prevent an accumulation of dust or dust leaks in process equipment. Keep all ignition sources away from this product. Dust collection equipment must be used in order to maintain dust levels below exposure limits Remove dust with fans or ventilation suction lines Housekeeping procedures must be adequate to minimize dust accumulation on equipment and indoor surfaces. Dust collection containers must be emptied carefully to minimize air-borne particles and exposure. Good personal hygiene practices must also be followed,
Extinguishing Media Special Fire Fighting Procedures SECTION 7. Stability & Reactivity Data Stability Incompatibilities Conditions to Avoid Hazardous Decomposition Products Hazardous Polymerzation SECTION 8. Special Precautions and Spill I Release or spill Precautions to be taken in handling and storage SECTION 9. Exposure Controls/ Personal Protection Engineering Controls Ventilation Procedure Work Practice Controls Respiratory Protection	dust layer - 170 degrees C Water, dry chemical, foam None, normal full protective gear with self-contained breathing apparatus as in any firefighting situation. Stable under ordinary conditions and use. Do not mix with oxidizers such as nitrate fertilizers, as this may initiate and/or accelerate combustion. Heat, sparks, open flames, oxidizing agents Oxides of carbon, sulfur, and nitrogen may be formed as a result of combustion. Will not occur Procedures Clean up and use per instructions or follow local, state and federal regulations for disposal of non-hazardous heat-dried sewage sludge. Keep biosolid pellets dry during storage, as moisture content that exceeds 10% (by weight) will cause spontaneous biological heating potentially leading to combustion. Equipment used to process biosolids pellets should be electrically bonded to ground. Use electrically conductive pneumatic transport lines to prevent static electricity discharge. Enclosed process equipment should contain relief vents, explosion suppression systems, and or an oxygen deficient atmosphere Prevent an accumulation of dust or dust leaks in process equipment. Keep all ignition sources away from this product. Dust collection equipment must be used in order to maintain dust levels below exposure limits Remove dust with fans or ventilation suction lines Housekeeping procedures must be adequate to minimize dust accumulation on equipment and indoor surfaces. Dust collection containers must be emptied carefully to minimize air-borne particles and exposure. Good personal hygiene practices must also be followed,
Special Fire Fighting Procedures SECTION 7. Stability & Reactivity Data Stability Incompatibilities Conditions to Avoid Hazardous Decomposition Products Hazardous Polymerzation SECTION 8. Special Precautions and Spill I Release or spill Precautions to be taken in handling and storage SECTION 9. Exposure Controls/ Personal Protection Engineering Controls Ventilation Procedure Work Practice Controls	dust layer - 170 degrees C Water, dry chemical, foam None, normal full protective gear with self-contained breathing apparatus as in any firefighting situation. Stable under ordinary conditions and use. Do not mix with oxidizers such as nitrate fertilizers, as this may initiate and/or accelerate combustion. Heat, sparks, open flames, oxidizing agents Oxides of carbon, sulfur, and nitrogen may be formed as a result of combustion. Will not occur Procedures Clean up and use per instructions or follow local, state and federal regulations for disposal of non-hazardous heat-dried sewage sludge. Keep biosolid pellets dry during storage, as moisture content that exceeds 10% (by weight) will cause spontaneous biological heating potentially leading to combustion. Equipment used to process biosolids pellets should be electrically bonded to ground. Use electrically conductive pneumatic transport lines to prevent static electricity discharge. Enclosed process equipment should contain relief vents, explosion suppression systems, and or an oxygen deficient atmosphere Prevent an accumulation of dust or dust leaks in process equipment. Keep all ignition sources away from this product. Dust collection equipment must be used in order to maintain dust levels below exposure limits Remove dust with fans or ventilation suction lines Housekeeping procedures must be adequate to minimize dust accumulation on equipment and indoor surfaces. Dust collection containers must be emptied carefully to minimize air-borne particles and exposure. Good personal hygiene practices must also be followed,
Special Fire Fighting Procedures SECTION 7. Stability & Reactivity Data Stability Incompatibilities Conditions to Avoid Hazardous Decomposition Products Hazardous Polymerzation SECTION 8. Special Precautions and Spill I Release or spill Precautions to be taken in handling and storage SECTION 9. Exposure Controls/ Personal Protection Engineering Controls Ventilation Procedure Work Practice Controls	dust layer - 170 degrees C Water, dry chemical, foam None, normal full protective gear with self-contained breathing apparatus as in any firefighting situation. Stable under ordinary conditions and use. Do not mix with oxidizers such as nitrate fertilizers, as this may initiate and/or accelerate combustion. Heat, sparks, open flames, oxidizing agents Oxides of carbon, sulfur, and nitrogen may be formed as a result of combustion. Will not occur Procedures Clean up and use per instructions or follow local, state and federal regulations for disposal of non-hazardous heat-dried sewage sludge. Keep biosolid pellets dry during storage, as moisture content that exceeds 10% (by weight) will cause spontaneous biological heating potentially leading to combustion. Equipment used to process biosolids pellets should be electrically bonded to ground. Use electrically conductive pneumatic transport lines to prevent static electricity discharge. Enclosed process equipment should contain relief vents, explosion suppression systems, and or an oxygen deficient atmosphere Prevent an accumulation of dust or dust leaks in process equipment. Keep all ignition sources away from this product. Dust collection equipment must be used in order to maintain dust levels below exposure limits Remove dust with fans or ventilation suction lines Housekeeping procedures must be adequate to minimize dust accumulation on equipment and indoor surfaces. Dust collection containers must be emptied carefully to minimize air-borne particles and exposure. Good personal hygiene practices must also be followed,

Data Sheet, reliable, however, it is your responsibility to determine the suitability of the information for your use. You are advised not to construe the information as absolutely complete since additional information may be necessary or desirable when particular, exceptional or variable conditions or circumstances exist or because of applicable laws or government regulations. Therefore, you should use this information only as a supplement to other information gathered by you, and you must make independent determinations of the suitability and completeness of the information from all sources to assure both proper use of the material described herein and the safety and health of employees. Accordingly, no guarantee is expressed or implied as to the results to be obtained based upon your use of this information.